

DATASHEET



 **DISTEC**
A FORTEC GROUP MEMBER

VIDEO WALL

SIMPLY INTEGRATE
VISUALISE YOUR CONTENT

Panel and housing

Panel Diagonal	[mm] / [Inch]	1168.4/ 46.0"		
Type		Video wall SNB monitor		
Bezel Width	[mm]	5.7 (monitor2monitor)		
Resolution	[Pixel]	1920 x 1080 FHD		
Max. input resolution	[Pixel]	3840 x 2160		
Calibration		White Point D65 and same brightness		
Luminance (center)	[cd/m²]	700		
Viewing angle	[°]	178 h / 178 v		
Backlight		LED		
Active area (H/V)	[mm]	1018.08 x 572.67		
Number of colors	[M]	1073.7		
Contrast ratio		4000:1		
Response time (on/off)	[ms]	6.5		
Pixel class		ISO 9241-307 (pixel error class II)		
Life time back light	[h]	50.000		
Continuous operating time	[h] / [d]	24/ 7		
Daisy Chain Spec.		4k 60 Hz	4k 30 Hz	FullHD 60 Hz
		9 units	16 units	25 units
Storage temperature	[°C] / [°F]	-10 ~ 60 / 14 ~ 140		
Operating temperature	[°C] / [°F]	0 ~ 40/ 32 ~ 104		
Storage humidity	[%]	30 ~ 80 (non condensing)		
Operating humidity	[%]	10 ~ 90 (non condensing)		
Panel orientation		Landscape and Portrait		
Location of connectors		Landscape: right (front view) Portrait: bottom		
Location of OSD buttons		Landscape: right (front view) Portrait: bottom		
Housing		Powdered steel sheet DC01, black RAL 9005		
Mounting	[mm]	VESA MIS-F 400 x 400 (M6)		
Mounting for accessoires	[mm]	VESA MIS-F 100 x 100 (M3)		
Power supply	[V]	AC 110 - 230		
Conformity		CE, FCC Class A, EU-RoHS		
Packaging		Single packaging for one way pallet (max. 4 packages p.p.)		
Package Contents		Safety instructions, driver CD, power cable		

Video Wall Monitor 46.0"



Video wall Super narrow bezel monitor




HDMI, DisplayPort, RS232

Video Wall 46" Video

Order number		DS-91-980
Interfaces		HDMI 2.0 in, HDMI 2.0 out, (4k Daisy Chain), RS232 in, RS232 out, DisplayPort 1.2 in, IR sensor
Power consumption (typ.)	[Watt]	130
Video wall functions		Edge suppression, tiling, daisy-chain cabling, PIP
Weight	[kg/ lb]	28.0/ 61.73
Dimensions (W x H x D)	[mm/ inch]	1024 x 579 x 86 40.31 x 22.80 x 3.38




Raspberry® IoT controller



POS-Line 46.0" IoT

Order number		DS-91-998
Order number OS		DS-60-859
Interfaces		1 x LAN, 2 x USB, 1 x HDMI, 1 x Line out, 1 x MicroSD card slot
Power consumption (typ.)	[Watt]	130
Weight	[kg/ lb]	28.0/ 61.73
Dimensions (W x H x D)	[mm/ inch]	1024 x 579 x 86 40.31 x 22.80 x 3.38



Electronic

Product	Order no.	Product description
Remote control	DS-92-019	OSD remote controll for Video wall displays 46"

Mounts and cable


Product	Order no.	Product description
Wall mount	recommendation	wall mount for walls: https://www.unicol.de/de/video-wall-loesungen.aspx
HDMI cable	KA-40-081	Cable HDMI 4k Typ A male/male 2m
DisplayPort cable	KA-40-105	Display Port 4k male/male 2m

Exercise caution when installing

It is only allowed to lift and transport the device by the handles. The frame of the panel-casing is only 0,3 mm. By lifting the device at the frame of the panel-casing, breakage of the glass, defaults of the slots or buckle of the case could be possible results. It is also not allowed to get the panel under pressure at the frontside.



Accessories



application examples of video walls at our customers



Contact

Our company network supports you worldwide with offices in Germany, Austria, Switzerland, Great Britain and the USA. For more information please contact:

HEADQUARTER - GERMANY



FORTEC Elektronik AG

Lechwiesenstraße 9
86899 Landsberg am Lech

Phone +49 81 91 9 11 72-0
E-Mail sales@fortecag.de
Internet www.fortecag.de

Designed,
developed and
made in Germany

FORTEC GROUP MEMBERS

GERMANY



Distec GmbH

Augsburger Str. 2b
82110 Germering

Phone +49 3 69 20 71 62-0
E-Mail solution@distec.de
Internet www.distec.de

AUSTRIA



FORTEC Elektronik AG

Office Vienna
Nuschingasse 12
1230 Wien

Phone +43 1 8 67 34 92-0
E-Mail office@fortec.at
Internet www.fortec.at

SWITZERLAND



ALTRAC AG

Bahnhofstraße 3
5436 Würenlos

Phone +41 44 7 44 61 11
E-Mail info@altrac.ch
Internet www.altrac.ch

UNITED KINGDOM



Display Technology Ltd.

Osprey House, 1 Sprey Court
Hichingbrooke Business Park
Huntingdon, Cambridgeshire
PE29 6FN

Phone +44 14 80 41 16 00
E-Mail info@displaytechnology.co.uk
Internet www.displaytechnology.co.uk

USA



Apollo Display Technologies, Corp.

87 Raynor Avenue,
Unit 1, Ronkonkoma
NY 11779

Phone +1 6 31 5 80 43 60
E-Mail info@apollodisplays.com
Internet www.apollodisplays.com

All figures are typical values. The real values of the panel may vary. The optical characteristics are determined after the panel has been „ON“ for approximately 30 minutes at an ambient temperature of 25° C (77° F).

Life time of the backlight is defined as the time to take until the brightness reduces to 50% of its original value.

Copyright 2019 Distec GmbH. Information in the document is subject to change without prior notice.