

DATASHEET



 **DISTEC**
A FORTEC GROUP MEMBER

POS-LINE 64.5

**SIMPLY INTEGRATE
VISUALISE YOUR CONTENT**

Panel and housing

POS-Line 64.5"

Panel Diagonal	[mm] / [Inch]	1639.1/ 64.53"
Type		Open -frame monitor (various bezels, true-flat glass and touch solutions are available under options)
Resolution	[Pixel]	1920 x 1080 FHD
Luminance (center)	[cd/m ²]	700
Viewing angle	[°]	178 h / 178 v
Backlight		LED
Active area (H/V)	[mm]	1428.48 x 803.52
Number of colors	[M]	1073.7 (PIIIA) 16.7 (PME, IQ Atom, IQ Core-i)
Contrast ratio		4000:1
Response time (on/off)	[ms]	8
Pixel class		ISO 9241-307 (pixel error class II)
Life time back light	[h]	60.000
Continuous operating time	[h]/ [d]	24/7
Mounting	[mm]	VESA MIS-F 800 x 400 (M6)
Storage temperature	[°C] / [°F]	-20 ~ 60/ -4 ~ 140
Operating temperature	[°C] / [°F]	0 ~ 40/ 32 ~ 104
Storage humidity	[%]	10 ~ 90 (non condensing)
Operating humidity	[%]	10 ~ 90 (non condensing)
Panel orientation		Landscape and Portrait
Location of connectors		Landscape: bottom Portrait: left (front view)
Location of OSD buttons		Landscape: bottom Portrait: left (front view)
Housing		Powdered steel sheet DC01, black RAL 9005
Power supply	[V]	AC 100 - 240
Conformity		CE, FCC Class A, EU-RoHS
Packaging		Single packaging for each piece including pallet
Package Contents		Safety instructions, driver DVD, power cable




Open frame monitor with bezel



VGA, HDMI, DisplayPort

POS-Line 64.5" Video PME


Order number		DS-91-954
Interfaces		1 x VGA, 1 x HDMI, 1 x DisplayPort, 1 x Audio Line-Out, 1 x USB-Remote, 1 x OSD 4 button
Power consumption (typ.)	[Watt]	190
Weight	[kg/ lb]	44.0/ 97.00
Dimensions (W x H x D)	[mm/ inch]	1480 x 855 x 122 58.27 x 33.66 x 4.80



VGA, DVI, S-Video, CVBS

POS-Line 64.5" Video PIIIA


Order number		DS-91-955
Interfaces		1 x VGA, 1 x DVI (HDMI via DVI), 1 x S-Video, 1 x Composite Video, 1 x RS232, 1 x OSD 4 button
Power consumption (typ.)	[Watt]	190
Weight	[kg/ lb]	44.0/ 97.00
Dimensions (W x H x D)	[mm/ inch]	1480 x 855 x 122 58.27 x 33.66 x 4.80




Network Mediaplayer

POS-Line 64.5" VideoPoster

Order number		DS-91-956
Interfaces		1 x LAN, 2 x USB, 1 x HDMI, 1 x Line out, 1 x MicroSD card slot
Power consumption (typ.)	[Watt]	181
Weight	[kg/ lb]	44.0/ 97.00
Dimensions (W x H x D)	[mm/ inch]	1480 x 855 x 122 58.27 x 33.66 x 4.80




Raspberry® IoT controller



POS-Line 54.6" IoT


Order number		DS-91-985
Order number OS		DS-60-859
Interfaces		1 x LAN, 2 x USB, 1 x HDMI, 1 x Line out, 1 x MicroSD card slot
Power consumption (typ.)	[Watt]	181
Weight	[kg/ lb]	44.0/ 97.00
Dimensions (W x H x D)	[mm/ inch]	1480 x 855 x 122 58.27 x 33.66 x 4.80



PC Intel® Atom

POS-Line 64.5" IQ Atom

Order number		DS-91-959
Interfaces		2 x LAN, 1 x USB 3.0, 3 x USB 2.0, 1 x HDMI, 1 x VGA, 1 x RS232
PC		CPU: Intel® Atom E3845 (1.9 GHz), Graphic: Intel® Valleyview SoC integrated Graphics RAM: 4 GB DDR3L, Storage: min. 120 GB mSATA
Fan		Fanless operation
Power consumption	[Watt]	200
Weight	[kg/ lb]	45.0/ 99.21
Dimensions (W x H x D)	[mm/ inch]	1480 x 855 x 122 58.27 x 33.66 x 4.80




PC Intel® Core™-i5



POS-Line 64.5" IQ Core-i

Order number		DS-92-026
Features		Resolution 4K external via DisplayPort supported
Interfaces		2 x DP, 2x LAN, 4x USB 3.0, 1 x Audio, 1 x MIC in
PC		CPU: Intel® Core™-i5-7300 U (2.6 GHz), Intel® HD Graphics GT series, RAM: 8GB DDR 4 Storage: 120 GB M.2Sata
Fan		No
Power consumption	[Watt]	210
Weight	[kg/ lb]	46.0/ 101.41
Dimensions (W x H x D)	[mm/ inch]	1480 x 855 x 122 58.27 x 33.66 x 4.80



Bezel/ Glass*

Order number		DS-91-951	DS-91-950
Name		Front bezel	Safety glass
Finish		Steel, powdered, black RAL 9005	Safety glass TSG, 5 mm anti glare
Can be combined with		Safety glass, ALS, Remote Control	Front bezel, ALS, Remote Control
Weight	[kg/ lb]	2.0/ 4.41	15.0/ 33.07
Dimensions of monitor with option (W x H x D)	[mm/ inch]	1484 x 859 x 123 58.43 x 33.82 x 4.84	1480 x 855 x 132 58.27 x 33.66 x 5.20
Dimensions of monitor with both options together (W x H x D)	[mm/ inch]	1484 x 859 x 133 58.43 x 33.82 x 5.24	

TrueFlat glass*

Order number		DS-91-952
Name		TrueFlat glass
Finish		Safety glass TSG, 5 mm anti glare with black passepartout
Can be combined with		—
Weight	[kg/ lb]	18.0/ 39.68
Dimensions of monitor with option (W x H x D)	[mm/ inch]	1540 x 917 x 130 60.63 x 36.10 x 5.12

*Cover glass an touches will reduce monitor brightness.

Electronic

Order number	DS-91-622
Name	Soundbar external
Description	Active speaker kit on the bottom
Details	2 x 1.25 Watt, 5V, USB digital audio input, power via USB
Can be combined with	with all front options except TrueFlat bezel
Available for controller	IQ Atom, IQ Core-i, VideoPoster

Options



Front bezel is a metal bezel for the open frame chassis and VESA mount.

Safety glass is an accessory for the open frame chassis. It covers and protects the TFT-panel.

Accessories

Electronic

Product	Order no.	Product description
Remote control	DS-91-621	OSD remote control for all displays of the Video PME and Video PIII Series
Ambient Light Sensor	DS-91-963	ALS for all displays of the Video PME, Video PIII and Video-Poster, can be combined with front bezel and safety glass
SSD Extension Atom	DS-91-997	Extension for SSD MSATA up to 240 GB for IQ Atom
RAM Extension Atom	DS-91-975	Extension for RMA up to 8 GB for IQ Atom
SSD Extension Core-i	DS-92-027	Extension for SSD M.2 up to 240 GB for IQ Core-i5
RAM Extension Core-i	DS-92-028	Extension for RMA up to 16 GB for IQ Core-i5

Accessories

External PC

Order number	DS-91-930
Name	PC-Box IQ Atom
Description	PC Module for external mounting
Interfaces	2 x LAN, 1 x USB 3.0, 3 x USB 2.0, 1 x HDMI, 1 x VGA, 1 x RS232
PC	CPU: Intel® Atom E3845 (1.9 GHz), Graphic: Intel® Valleyview SoC integrated Graphics RAM: 8 GB DDR3L, Storage: min. 120 GB mSATA
Available for controller	Video PME, Video PIIIA, VideoPoster
Fan	Fanless operation
Weight [kg/ lb]	1.7/ 3.75
Dimensions [mm/ inch]	240 x 260 x 50/ 9.45 x 10.24 x 1.97
Power supply	DS-91-945 for operate the PC box as stand alone device without display for maintenance, 12V/ 60 W



Optional removable PC box with Intel Atom CPU. The PC box can be removed without taking the display down from the wall.

Order number	DS-92-033
Name	PC Box extern IQ Core-i5 DFI KU173
Description	PC Module for external mounting
Interfaces	2 x DP, 2x LAN, 4x USB 3.0, 1 x Audio, 1 x MIC in
PC	CPU: Intel® Core™-i5- 7300 U(2.6 GHz), Intel® HD Graphics GT series, RAM: 8GB DDR 4 Storage: 120 GB M.2Sata
Available for controller	Video PME, PIIIA
Fan	No
Weight [kg/ lb]	2.6/ 5.73
Dimensions [mm/ inch]	240 x 257 x 48.5/ 9.45 x 10.24 x 1.97
Power supply	DS-91-945 for operate the PC box as stand alone device without display for maintenance, 12V/ 60 W



Optional removable PC box with Intel Core-i5 CPU. The PC box can be removed without taking the display down from the wall.

Mounts and Covers

Product	Order no.	Product description
Wall mount	DS-91-101	Titling wall mount for all displays from 46" up to 64.5"
Protective cover	DS-91-604	Installed on top of the display, dust shield prevents liquid or falling dust from penetrating the electronic part of the monitor via the upper air vents
Cable cover for connectors	DS-91-960	Cover for the cable connectors to prevent unauthorized persons from removing or plugging cables. For all POS-Line displays of the PME, PIII and VPIII 64.5"
Cable cover for connectors	DS-91-961	Cover for the cable connectors to prevent unauthorized persons from removing or plugging cables. For all POS-Line displays of the IQ Series 64.5". Also suited for optional PC boxes DS-91-426, DS-91-427 and DS-91-930.
Cable cover for connectors	DS-91-962	Cable cover. Only available in combination with covers DS-91-960 and DS-91-961.
Display Port cable	KA-40-105	Cable Display Port 1.2 4k male/male 2m

Accessories

Operating systems, Software

Product	Order no.	Product description
Windows 7 embedded 32 bit DE	DS-60-645	Operation system only for Atom
Windows 7 embedded 32 bit EN	DS-60-650	Operation system only for Atom
Windows 7 FES 64 bit DE	DS-60-725	Operation system only for Atom
Windows 7 FES 64 bit EN	DS-60-781	Operation system only for Atom
Windows 10 Pro. 64 bit DE	DS-60-811	Operation system
Windows 10 Pro. 64 bit EN	DS-60-810	Operation system
Windows 10 IOT ATOM DE/ EN	DS-60-864	Operation system
Windows 10 IOT CORE-I DE/ EN	DS-60-865	Operation system
WEBPOSTER	DS-60-787	WEBPOSTER embedded Linux

Various accessories are available for POS-Line monitors.

All monitors can be customized according to your specific requirements.

Please contact our sales team if you are interested in product modifications or custom designs.



Contact

Our company network supports you worldwide with offices in Germany, Austria, Switzerland, Great Britain and the USA. For more information please contact:

HEADQUARTER - GERMANY



FORTEC Elektronik AG

Lechwiesenstraße 9
86899 Landsberg am Lech

Phone +49 81 91 9 11 72-0
E-Mail sales@fortecag.de
Internet www.fortecag.de

Designed,
developed and
made in Germany

FORTEC GROUP MEMBERS

GERMANY



Distec GmbH

Augsburger Str. 2b
82110 Germering

Phone +49 3 69 20 71 62-0
E-Mail solution@distec.de
Internet www.distec.de

AUSTRIA



FORTEC Elektronik AG

Office Vienna
Nuschinggasse 12
1230 Wien

Phone +43 1 8 67 34 92-0
E-Mail office@fortec.at
Internet www.fortec.at

SWITZERLAND



ALTRAC AG

Bahnhofstraße 3
5436 Würenlos

Phone +41 44 7 44 61 11
E-Mail info@altrac.ch
Internet www.altrac.ch

UNITED KINGDOM



Display Technology Ltd.

Osprey House, 1 Sprey Court
Hichingbrooke Business Park
Huntingdon, Cambridgeshire
PE29 6FN

Phone +44 14 80 41 16 00
E-Mail info@displaytechnology.co.uk
Internet www.displaytechnology.co.uk

USA



Apollo Display Technologies, Corp.

87 Raynor Avenue,
Unit 1, Ronkonkoma
NY 11779

Phone +1 6 31 5 80 43 60
E-Mail info@apolloDisplays.com
Internet www.apolloDisplays.com

All figures are typical values. The real values of the panel may vary. The optical characteristics are determined after the panel has been „ON“ for approximately 30 minutes at an ambient temperature of 25° C (77° F).

Life time of the backlight is defined as the time to take until the brightness reduces to 50% of its original value.

Copyright 2019 Distec GmbH. Information in the document is subject to change without prior notice.